Fujitsu recommends Windows 8 Pro.

Data Sheet
Fujitsu ESPRIMO Q910
Desktop PC

The Mini with More PC per cm³

The Fujitsu ESPRIMO Q910 delivers excellent performance, energy efficiency and manageability in a mini PC. An Intel® Core™ processor and Intel® vPro™ technology deliver professional computing and management. Its stylish design is also practical, with two front USB 3.0 ports for lightning fast connections

An elegant mini PC for the modern office environment
Eye-catcher on your desk with a modern and exclusive design
■ Fully equipped PC with a volume of only 1.9 liters - based on standard desktop technology

Black shell and a green core
Needs only 10 watts in idle-mode and saves valuable resources
■ Smart desktop technology for lowest power consumption, optional PVC free system and an up to 90% energy efficient onboard power supply, halogen-free mainboard

Unleash the power
Latest Intel® technology to support your challenging business applications
■ 3rd generation Intel® Core™ processor family

Sophisticated system management
Simple system administration in complex IT infrastructures
■ Intel® vPro™ technology (depending on processor) and DeskView manageability

Superb usability
Pleasant working environment due to a tidy desk
■ Horizontal or vertical operations and an integrated VESA mount, service door for easy upgrade of major components

reddot design award winner 2012

ENERGY STAR

epeat GOLD

NORDIC ECOLABEL

TLA Technology Leadership Awards 2012

Components

Processor	Intel® Core™ i5-3470T processor (2 Cores / 4 Threads, 2.90 GHz, up to 3.6 GHz, 3 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i3-3220T processor (2 Cores / 4 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Pentium® processor G2020T (2 Cores / 2 Threads, 2.50 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1610T (2 Cores / 2 Threads, 2.30 GHz, 2 MB, Intel® HD Graphics)
	Intel® vPro™ Logo with Intel® Core i5 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Operating systems	
Operating system	Windows 8 Pro Windows 8 Windows® 7 Professional 64-bit Windows® 7 Professional 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Home Basic 32-bit (EM)
Operating system compatible	Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM
	4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM
	8 GB (1 module(s) 8 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM
Hard disk drives (internal)	SSD SATA III Premium, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA II, 7200 rpm, 320 GB, 2.5-inch
	HDD SATA II, 5400 rpm, 1000 GB, 2.5-inch*
	HDD SATA II, 5400 rpm, 750 GB, 2.5-inch*
	HDD SATA II, 5400 rpm, 500 GB, 2.5-inch*
	HDD SATA II, 5400 rpm, 320 GB, 2.5-inch*
Hard disk notes	*Disk imaging software of the customer must be 4k sector size / advanced format ready Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	DP to DVI-D (single link) Adapter Cable
Drives (optional)	BD Triple Writer SATA Slot-in slim
	DVD Super Multi Slot-in slim
Interface add on cards/components (optional)	
	WLAN 802.11 b/g/n (2x2) and Bluetooth (dedicated regions only)
Base unit	ESPRIMO Q910
Mainboard	
Mainboard type	D3183
Formfactor	proprietary
Chipset	Intel® Q77
Processor socket	LGA 1155
Processor quantity maximum	1

Mainboard

Memory slots	2 SO DIMM (DDR3, 1600 MHz)
Supported capacity RAM (max.)	16 GB
Memory frequency	1600 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same
LAN	10/100/1000 MBit/s Intel® 82579 LM
Integrated WLAN	1 (optional)
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Buzzer

I/O controller on board

Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-out / headphone	1
Audio: line-in / microphone	1
USB 2.0 total	2
USB 3.0 total	4
USB front	2x 3.0
USB rear	2x 2.0 and 2x 3.0
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Ethernet (RJ-45)	1
Kensington Lock support	1
Multicardreader	1 (SD, MMC, MS, XD)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB wheel mouse
Input devices (optional)	KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim slot-in

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500 (depending on processor)
Shared video memory	up to 1759 MB

Graphics on board

TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL® 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 115V/230V; 10% / 20% / 50% / 100% load) : 86% / 87% / 90% / 90%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	65 W (integrated in system)
Power factor correction/active power	No (meets input harmonic current according EN61000-3-2)
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=ae3a2536-3eb0-4982-bea2-9acda2263e13

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption

Noise emission

Related Processors for noise	Intel® Core™ i5 3470T
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	4.7 B / 31 dB(A) Bystander ; 34 dB(A) Operator position

Noise emission

Standard noise operation mode: HDD load	3.3 B / 20 dB(A) Bystander ; 22 dB(A) Operator position
Standard noise operation mode: Idle mode	SSD: no noise emmision, 2.5" HDD: 3.1 B / 19 dB(A) Bystander ; 21 dB(A) Operator position
Standard noise operation mode: ODD load	4.7 B / 33 dB(A) Bystander ; 34 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	SSD: no noise emmision, 2.5" HDD: 3.2 B / 19 dB(A) Bystander ; 21 dB(A) Operator position
Blue angel noise emission according certification	for max. possible configuration According to ISO 7779:2010, ECMA-74
Blue angel noise notes / description	A-weighted sound power level Lwad (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.3 B = 33 dB
Blue angel noise operation mode: Idle mode	3.1 B = 31 dB
Blue angel noise operation mode: ODD load	4.7 B = 47 dB

Dimensions / Weight / Environmental

Dimensions (W x D x H)	185 x 188 x 54 mm 7.29 x 7.41 x 2.13 inch
Operating position	Vertical / horizontal (no feet needed)
VESA mount	integrated (100mm), applicable for selected monitors only, additional mounting kit for specific monitors optional
Weight	1.6 kg
Weight (lbs)	3.53 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 ℃ (50 - 95 ℉)

Compliance

Product	ESPRIMO Q910
Model	MPC2
Germany	TÜV GS Blauer Engel / Blue Angel
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 (dedicated regions) EPEAT® Gold (dedicated regions)
Compliance notes	This product is free of poly®vinyl chloride (PVC) when ordered with the optional PVC free power cord
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) Anti Virus software (60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Compatibility (references)

	DMI 2.0
	PC 2001
	WMI 1.5
	USB 2.0
	SMBIOS

Manageability

Manageability technology	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	Intrusion switch (optional)
	iAMT 8.0 (depending on CPU)
	WoL (Wake on LAN)
Manageability software	DeskView Client
	DeskView Instant BIOS Management
	DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management
	BIOS Management
	Driver Management
	Security Management
	Alarm Management
Manageability link	http://www.fujitsu.com/fts/manageability

Security

Physical Security	Kensington Lock support
	Intrusion switch (optional)
	Housing Lock Plate (to use with Kensington lock)
System and BIOS Security	EraseDisk (optional)
	Boot sector virus protection
	Write protect option for the Flash EPROM
	Embedded security (TPM 1.2)
	Control of all USB interfaces
	External USB ports can be disabled separately
	Control of external interfaces
User Security	User and supervisor BIOS password
	Hard disk password
	Access protection via external SmartCard reader (optional)

Packaging information

Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	If keyboard is inlcuded in packaging: 1.)packaging dimension is increasing to: 500 x 208 x 290mm / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 49; printed user documentation is bleached in chlorin free process;

Warranty

Standard Warranty	3 years (depending on country)
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 2 years material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Maintenance and Support Services - the perfect extension

Warranty	
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

USB 3.0 Port Replicator PR08		The Fujitsu USB 3.0 Port Replicator PR08 is the solution for notebooks without a dedicated docking connector or in hot-desk environments. You can connect to the local area network, and to all of your peripherals with a single USB 3.0 plug and boost your productivity by extending your workspace over up to four displays.	Order Code: S26391-F6007-L400
Display B22W-6 LED proGREEN		The B22W-6 LED proGREEN offers best ergonomics and usability for intensive office use with a 4-in-1 stand.	Order Code: S26361-K1392-V160
CELVIN® Drive M200		The CELVIN Drive M200 is an ultra-portable and high-class storage device. Since it is compatible with USB3.0 and USB 2.0, it can be used with a large variety of devices. It is ideal for notebook and desktop users. It makes data backup easier and faster than ever.	Order Code: S26341-F103-L500
SOUNDSYSTEM DS E2000 Air		The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
Wireless Keyboard Set LX900		The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.	S26381-K564-L4** (**: Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO Q910, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO Q910, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.